

Hemsun Analytics

C-101, Ganesh Greens
Near Vandematram, GST Road,
Chenpur, Ahmedabad - 382470
Tel: +91 7383 4660 60/70
Email: info@hemsun.co.in



COMPLETE RANGE OF INDUSTRIAL DIGITAL LUX METER

Digital Lux Meter HLM 2000



Features

- Automatic and manual function
- Maximum, Minimum function
- Data hold
- Peak hold
- Relative measurement (Zero)
- Unit conversion: FC/LUX
- Display: 3 1/2 bit LCD display, maximum reading is 1999. And with analog bar display.
- Over load range tips; When the measured value exceeds the current range, the display will appear "1"/"FF"
- Photo range: 20,200,2000,20000,200000 LUX 20,200,2000,20000FC
- Low power alarm
- Auto power off
- Key voice indication
- Dimensions :190*89*42.5mm
- Weight:360g

Technical Specifications

Measurement range	20,200,2000,20000,200000 LUX 20,200,2000,20000FC	
Accuracy	±3%(According to the ordinary incandescent lamp when calibrated at 2854K)	
Sample rate	≥2times/sec	
Unit conversion	FC/LUX	
Display	3 1/2 bit LCD display, maximum reading is 1999. And with analog bar display.	
Over load range tips	When the measured value exceeds the current range, the display will appear "1"/"FF"	
Battery time	200 hours	
Battery	9V DC	
Cosine angle deviation feature	Cosine angle	Error
	30°C ±2%	±2%
	60°C ±6%	±6%
Operation temp & humidity	0~40°C(<80%RH)	
Storage temp & humidity	-10~60°C(<70%RH,Removed battery)	
Dimensions	190*89*42.5mm	
Weight	360g	

For Any More Query Regarding Product, please contact us or write us on info@hemsun.co.in

The Above Specifications are standard for reference only. Product specifications and measuring ranges can be customize and supplied as per user confirmation.

Note: Specification and Features mentioned in datasheet will be change with application, Cause of Engineering Research, Design And Product Improvement; specifications are subjected to change without notice. Refer latest datasheet on website : www.hemsun.co.in